

Option Selection Guide

Notes: S= Standard	Model and Option Numbers														
	1073	1083	1084			1088	1092			1093			1094	1095	
Option Description	A	B	A	B	C	B	A	B	C	A	B	C	B	A	C
I/O															
Four Additional Configurable Outputs			03	03	03	03				03	03	03			
Parallel BCD Output			06	06	06	04									
BCD with Second RS-232 Port			17	17	17	17									
Second RS-232 Port			19	19	19	17A	19	19	19	19	19	19	S	S	S
Self-Monitor, IRIG-B Distribution System and Second RS-232 Port						18									
Out-of-Lock Relay 1 Form C (SPDT)			S	S	S	19	93	93	93	93	93	93	S	S	S
Fiber-Optic Output			20	20	20										
Four Configurable Fiber-Optic Outputs			20A	20A	20A	20A				20A	20A	20A			
COMTRADE Sample Rate Generator			23	23	23	23									
Frequency Measurement Capability			09												
Sine Wave Outputs (1M, 5M, 10M Hz)			xy												
8-Channel High-Drive IRIG-B Output			27	27	27	27				27	27	27			
Power System Time, Frequency and Phase Monitor			28	28	28	28				28	28	28			
Four Additional Outputs with Dry Contact and +25/50 Vdc			29	29	29	29				29	29	29			
Network Time Protocol (NTP) / Precision Time Protocol (PTP), IEEE 1588 Server			34	34	34	34				34	34	34			
IRIG-B Modulated Output			S	S	S	S	92	92	92	92	92	92	S	S	S
RS-422/485 Driver			S	S	S		94	94	94	94	94	94	S	S	S
Fiber-Optic Input			01												
Power															
Terminal Power Strip						07									
10 to 60 Vdc with Terminal Power Strip						08									
Surge Withstand & Terminal Strip, 110 to 170 Vdc						15A									
Surge Withstand & Terminal Strip, 110 to 300 Vdc						15B									
IEC-320 Power Inlet, 85 to 264 Vac, 110 to 350 Vdc	07	S	07	07	07	S				07	07	07	07		
10 to 60 Vdc Power, Terminal Strip, Surge Withstand Capability	08		08	08	08					08	08	08	08		
85 to 264 Vac, 110 to 350 Vdc Power Strip, SWC	10		10	10	10					10	10	10	10		
Oscillator and Timing															
OCXO and 4 Additional Configurable Outputs						12									
General															
LCD Backlight					01	01	01	01			01	01	S		
GPS Data Backup Battery		S	S	S	S	S	S	S	S	S	S	S	S	S	S
On/Off Switch	04		04	04		S				04	04		S		
CE Mark/Label	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S